

BOSHART INDUSTRIES

Telephone: 1-519-595-4444 - Toll Free: 1-800-561-3164

Fax: 1-519-595-4380 - www.boshart.com

SECTION 10 CHECK & FOOT VALVES

PRODUCT LINE	PAGE
Bronze or Brass Check Valve	1
Stainless Steel Check Valve	2
Swing Check Valve	2
Flomatic Check Valves	3
Plastic Check Valves	5
PVC In-Line Check Valves	5
Model 70 - Auto-Drain Valve	5
Iron Check Valves	6
Break Off Plug	7
Ball Check	7
Cast Iron Check Valves	8
Foot Valves	9
Bronze Foot Valves	9
Stainless Steel Foot Valves	9
Flomatic Foot Valves	9
Cast Iron Foot Valves	9
Seal Well Foot Valves	10
PVC Foot Valves	10
Cast Iron Flanged Foot Valves	11
Y-Strainer	11

BOSHART INDUSTRIES

Telephone: 1-519-595-4444 - Toll Free: 1-800-561-3164


Fax: 1-519-595-4380 - www.boshart.com

10-1

August 1/18

NO LEAD CHECK VALVES

- Available in cast bronze or cast brass body and poppet
- NBR "O"-Ring Seal (Nitrile Buna-N)



SIZE	NO LEAD BRONZE		NO LEAD BRASS		WGT lbs	QUANTITY	
	PART NO.	LIST PRICE-A	PART NO.	LIST PRICE-A		CTN	CASE
1/2"	17CV050NL	15.03	17YBCV050NL	12.30	0.50	10	100
3/4"	17CV075NL	19.65	17YBCV075NL	16.69	0.50	10	80
1"	17CV100NL	27.58	17YBCV100NL	23.10	0.75	10	60
1-1/4"	17CV125NL	44.82	17YBCV125NL	31.75	1.25	5	40
1-1/2"	17CV150NL	50.86	17YBCV150NL	44.42	1.50	5	30
2"	17CV200NL	103.56	17YBCV200NL	72.79	2.75	5	20
3"			17YBCV300NL	312.62	9.55	1	6
4"			17YBCV400NL	628.37	18.37	1	3



Temp.Max. 180°F (80°C)
Pressure Max 200 PSI



MALE X FEMALE

1-1/4" MPT X 1" FPT	17CVMF-125-100NL	48.03				10	60
---------------------	------------------	-------	--	--	--	----	----

NO LEAD BRASS CONTROL CENTRE CHECK VALVES

PART NO	SIZE	TAPPING(S) INLET SIDE	TAPPING(S) OUTLET SIDE	OUTER DIA.	LENGTH	WGT lbs	LIST PRICE-A
SERIES "A" Cast Brass body and poppet, NBR "O"-Ring Seal (Nitrile Buna-N)							
17YBCVA-100NL	1"	(1) 1/8" FPT	None	1.75"	3.25"	0.96	19.11
17YBCVA-125NL	1-1/4"	(1) 1/8" FPT	None	2.25"	3.87"	1.30	30.64
SERIES "B" Cast Brass body and poppet, NBR "O"-Ring Seal (Nitrile Buna-N)							
17YBCVB-100NL	1"	(1) 1/8" FPT	(1) 1/4" FPT	1.75"	3.25"	0.96	22.63
17YBCVB-125NL	1-1/4"	(1) 1/8" FPT	(1) 1/4" FPT	2.25"	3.87"	1.30	31.13
17YBCVB-150NL	1-1/2"	(1) 1/8" FPT	(1) 1/4" FPT	2.50"	4.25"	1.80	35.30
17YBCVB-200NL	2"	(1) 1/8" FPT	(1) 1/4" FPT	3.12"	5.00"	2.80	70.65
SERIES "C" Cast Brass body and poppet, NBR "O"-Ring Seal (Nitrile Buna-N)							
17YBCVC-100NL	1"	(1) 1/8" FPT	(2) 1/4" & (1) 1/8 FPT comes with plug	1.75"	3.25"	0.96	20.57
17YBCVC-125NL	1-1/4"	(1) 1/8" FPT	(2) 1/4" & (1) 1/8" FPT comes with plug	2.25"	3.87"	1.30	32.16



Valves do not include items shown in pictures

Temp.Max. 180°F (80°C) Pressure Max 200 PSI

BOSHART INDUSTRIES

10-2
August 1/18

Telephone: 1-519-595-4444 - Toll Free: 1-800-561-3164
Fax: 1-519-595-4380 - www.boshart.com

STAINLESS STEEL CHECK VALVE

Boshart recommends -

- #304 Stainless Steel body
- #304 Stainless Steel poppet
- Viton "O" Ring seal

Using both Gray Stainless Steel PTFE Tape & Gray Magic Pipe Thread Compound together for joining stainless steel threaded connections.



SIZE	PART NO.	WGT lbs	QUANTITY		LIST PRICE-A
			CTN	CASE	
1/2"	17CVSS-050	0.40	10	100	22.64
3/4"	17CVSS-075	0.50	10	80	29.99
1"	17CVSS-100	0.75	10	60	42.10
1-1/4"	17CVSS-125	1.15	5	40	56.40
1-1/2"	17CVSS-150	1.40	5	30	76.26
2"	17CVSS-200	2.75	5	20	128.68
3"	17CVSS-300	8.75	1	6	539.69
4"	17CVSS-400	17.75	1	3	960.81



Temp Max 180°F (80°C)
Pressure Max 200 PSI



MALE X FEMALE

1-1/4" MPT X 1" FPT	17CVSSMF-125-100	0.80	10	60	56.20
---------------------	------------------	------	----	----	-------

FLOMATIC® VALVES MODEL 80SS - FEMALE X FEMALE STAINLESS STEEL CHECK VALVE

- #303 Stainless Steel body
- Stainless Steel spring and poppet
- Nitrile (Buna-N) seal

SIZE	PART NO	WEIGHT	CASE QTY	LIST PRICE-A
1"	17-4201SS2	1.10	50	74.15
1-1/4"	17-4202SS2	1.41	36	104.47



Temp Max 180°F (80°C)
Pressure Max 400 PSI

FLOMATIC® VALVES MODEL 80S6 - FEMALE x FEMALE STAINLESS STEEL CHECK VALVE

- #316 Stainless Steel Body
- Stainless Steel spring and poppet
- Viton seal


SIZE	PART NO	WEIGHT LBS	CASE QTY	LIST PRICE-A
1"	17-4031S6	1.10	50	134.46
1-1/4"	17-4032S6	1.39	36	198.73
1-1/2"	17-4033S6	1.20	25	260.47
2"	17-4034S6	3.97	16	387.72
3"	17-7938S6-PLG	10.01	5	1507.28
4"	17-7939S6-PLG	24.91	4	2206.42



Temp Max 400°F (200°C)
Pressure Max 400 PSI

NO LEAD BRASS SWING CHECK VALVE

- Max. Working Pressure 200 PSI Water, Oil & Gas (Cold Water, Non-shock)
- Cast Brass body, disc and cap
- Brass rod pin and screw
- Max. Working Temperature 212°F (100°C)
- Threads to ANSI B1.20.1
- CxC to ANSI B16.18



SIZE	PART NO. IPS	LIST PRICE-A	QUANTITY CTN	CASE	PART NO. CXC	LIST PRICE-A	PORT SIZE INCH	QUANTITY CTN	CASE
1/2"	08060311NL	13.15	10	120	08060312NL	13.15	0.52	10	120
3/4"	08060411NL	17.37	10	80	08060412NL	17.37	0.75	10	80
1"	08060511NL	23.03	5	60	08060512NL	23.03	0.93	5	60
1-1/4"	08060611NL	38.82	5	40	08060612NL	38.82	1.25	5	40
1-1/2"	08060711NL	50.19	5	30	08060712NL	50.19	1.38	5	30
2"	08060811NL	82.79	2	24	08060812NL	82.79	1.81	2	24
2-1/2"	08060911NL	142.20	1	15	08060912NL	142.20	2.36	1	15
3"	08061011NL	202.07	1	6	08061012NL	202.07	2.56	1	6
4"	08061111NL	307.54	1	4			3.54		



BOSHART INDUSTRIES

Telephone: 1-519-595-4444 - Toll Free: 1-800-561-3164

Fax: 1-519-595-4380 - www.boshart.com


10-3

December 4/15

FLOMATIC® VALVES MODEL 80E - FEMALE x FEMALE CHECK VALVE

- Cast body construction / Stainless Steel spring
- Nylon poppet c/w NITRILE (Buna-N) seal


SIZE	PART NO.	WGT lbs	CASE QTY	LIST PRICE-A
1/4"	17-5118E	0.2	10	91.59
3/8"	17-5159E	0.2	10	92.07



Temp Max 180°F (80°C)
Pressure Max 200 PSI

- Lead free bronze (FEDERALLOY #1) body
- Threaded female x female connection
- Non-Spin Acetal poppet
- Nitrile (Buna-N Seal)
- Stainless steel spring

SIZE	PART NO.	WGT lbs	CASE QTY	LIST PRICE-A
1/2"	17-4029E	0.2	100	67.00
3/4"	17-4030E	0.7	100	67.84
1"	17-4031E	1.3	100	71.98
1-1/4"	17-4032E	1.6	36	102.54
1-1/2"	17-4033E	2.5	25	143.83
2"	17-4034E	3.1	16	229.13
2-1/2"	17-4035E *	6.5		958.68
3"	17-4036E *	13.0	1	1155.28
4"	17-4037E *	24.0	1	2008.54



Temp Max 180°F (80°C)
Pressure Max 400 PSI

* 2-1/2" to 4" Unleaded Bronze Poppet


FLOMATIC® VALVES MODEL GF8080E/GF8080S6 - DUAL CHECK VALVE WITH SINGLE UNION

Design for installation on potable water lines to protect against both back-siphonage and backpressure of polluted water into the potable water supply

- Acetal poppet
- Nitrile (Buna-N) o-ring seal
- Stainless steel spring
- Complies with ASSE 1024

SIZE	PART NO.	WGT lbs	CASE QTY	LIST PRICE-A
No Lead Brass Body				
1/2"	17-GF8089E	2		104.05
3/4"	17-GF8080E	2	25	109.67
1"	17-GF8081E	2		123.26

316 Stainless Steel Body				
3/4"	17-GF8080S6	2		209.79
1"	17-GF8081S6	2		218.43




Temp Max 180°F (80°C)
Pressure Max 175 PSI

FLOMATIC® VALVES MODEL 100ME - MALE x FEMALE CHECK VALVE

- Submersible pump check valve
- Hex shaped for easy wrenching
- Nitrile (Buna-N Seal)
- Lead free bronze (FEDERALLOY #1) body
- Stainless Steel spring
- Threaded male x female connection
- Non spin acetal poppet

SIZE	PART NO.	WGT lbs	CASE QTY	LIST PRICE-A
1-1/4" M x 1" F	17-4221LE *	1.1	50	72.23
1-1/4" M x 1-1/4" F	17-4242E	1.5	36	91.31
1-1/2" M x 1-1/4" F	17-4223E	1.5	36	121.44



Temp Max 180°F (80°C)
Pressure Max 400 PSI

* Longer threads for use with PVC pipe.

BOSHART INDUSTRIES


10-4
December 4/15

Telephone: 1-519-595-4444 - Toll Free: 1-800-561-3164
Fax: 1-519-595-4380 - www.boshart.com

FLOMATIC® VALVES MODEL 80ME - MALE x FEMALE CHECK VALVE

- Submersible pump check valve
- Lead free bronze (FEDERALLOY #1) body
- Non-spin acetal poppet
- Nitrile (Buna-N Seal)

SIZE	PART NO.	WGT lbs	CASE QTY	LIST PRICE-A
1" M x 1" F	17-4071E	0.7	49	76.49
2" M x 2" F	17-4079E	2.5	16	237.49




Temp Max 180°F (80°C)
Pressure Max 400 PSI

FLOMATIC® VALVES MODEL 100XLE - CHECK VALVE WITH X-LONG THREADS

- Extra length threads (MPT x FPT) specially designed with extended pipe lead-in for installing PVC drop pipe
- Lead free bronze (FEDERALLOY #1) body
- Acetal poppet c/w Nitrile (Buna-N) seal
- Hex shaped for easy wrenching
- Stainless Steel spring
- Full-ported field proven design

SIZE	PART NO.	QUANTITY CTN	CASE	LIST PRICE-A
1" MPT X 1" FPT	17-4201XLE	1	36	87.01
1-1/4" MPT X 1-1/4" FPT	17-4242XLE	1	36	112.03




Temp Max 180°F (80°C)
Pressure Max 400 PSI

FLOMATIC® VALVES MODEL 80HTE - FEMALE x FEMALE HIGH TEMPERATURE CHECK VALVE

- Threaded female x female connections
- High temperature nickel plated poppet
- EPDM seal, stainless steel spring
- Ideal for hot water applications

SIZE	PART NO.	WGT lbs	LIST PRICE-A
1/2"	17-4029HTE	0.2	89.32
3/4"	17-4030HTE	0.8	124.66
1"	17-4031HTE	1.4	121.07
1-1/4"	17-4032HTE	1.7	166.56
1-1/2"	17-4033HTE	2.7	231.73
2"	17-4034HTE	4.0	328.64




Temp Max 300°F (145°C)
Pressure Max 100 PSI

FLOMATIC® VALVES MODEL 100E - FEMALE x FEMALE CHECK VALVE

- Lead free bronze (FEDERALLOY #1) body
- Hex shaped for easy wrenching
- Non-Spin Acetal poppet
- Nitrile (Buna-N Seal)
- Stainless Steel spring

SIZE	PART NO.	WGT lbs	CASE QTY	LIST PRICE-A
1"	17-4201E	1.1	50	66.78
1-1/4"	17-4202E	1.4	36	94.75



Temp Max 180°F (80°C)
Pressure Max 400 PSI

BOSHART INDUSTRIES

Telephone: 1-519-595-4444 - Toll Free: 1-800-561-3164

Fax: 1-519-595-4380 - www.boshart.com

10-5

September 25/17

FLOMATIC® VALVES MODEL 297D - FEMALE x FEMALE PLASTIC CHECK VALVE

- Plastic (Acetal) body / Stainless Steel spring
- Nylon 11 poppet c/w VITON seal
- Threaded female x female connection



SIZE	PART NO.	WGT oz	CASE QTY	LIST PRICE-A
3/8"	175359	0.04 oz	10	42.67
1/2"	175239	0.06 oz	1	55.32



FLOMATIC® VALVES MODEL 290P - FEMALE x FEMALE PLASTIC CHECK VALVE

- Polypropylene body / Stainless Steel spring
- Polypropylene poppet c/w viton seal
- Threaded female x female connection

SIZE	PART NO.	WGT oz	QUANTITY CTN	CASE	LIST PRICE-A
1/2"	175357	0.06 oz	1	10	53.74
3/4"	175358	0.06 oz	1	10	86.30

Temp Max 200°F (90°C)
Pressure Max 150 PSI



PVC CHECK VALVES

- One piece "Extra Heavy Duty" valve body molded from Rigid PVC, listed under NSF61 & NSF14 (ASTM D-1784) provides superior tensile strength.
- FPT threads to ASME /ANSI B 1.20.1 specifications.
- Robust stainless steel poppet and hardware.
- NBR Sealing Gasket ensures a positive seal.
- Flow diverter minimizes turbulence and friction loss.
- Stainless Steel spring closes valve against pressure, eliminating flow reversal & minimizing hydraulic shock.
- Stemless acetal poppet guide for long-lasting, quiet, trouble free operation in both vertical and horizontal installations.



PART NO.	SIZE	OUTSIDE DIA.	LENGTH	WEIGHT LBS	CARTON QTY	LIST PRICE-A
17PCV075	3/4"	1.599"	2.905"	0.161	20	7.28
17PCV100	1"	1.912"	3.455"	0.255	20	8.13
17PCV125	1-1/4"	2.364"	3.920"	0.436	20	10.34
17PCV150	1-1/2"	2.660"	4.012"	0.53	20	14.98
17PCV200	2"	3.288"	4.646"	0.92	10	22.52

Ratings: Max. Working Pressure: 150 psi at 73°F (1034 kPa @ 22°C), Designed for cold water applications, for hot water applications, special high temperature valves must be used - Consult Factory.



PVC IN-LINE CHECK VALVES

- Durable PVC body / 304 Stainless Steel spring
- PVC poppet c/w EPDM seal



Max. Working Pressure: 100 PSI at 73°F (23°C)
Temp Max 140°F (60°C)

SIZE	PART NO. THREADED	LIST PRICE-A	PART NO. SOCKET	LIST PRICE-A	WGT lbs each	CASE QTY
1/2"	1710-05	5.60	1710S-05	5.60	0.19	120
3/4"	1710-07	6.13	1710S-07	6.13	0.20	120
1"	1710-10	8.97	1710S-10	8.97	0.40	80
1-1/4"	1710-12	11.98	1710S-12	11.98	0.69	60
1-1/2"	1710-15	12.39	1710S-15	12.39	0.70	60
2"	1710-20	14.98	1710S-20	14.98	1.34	40
3"	1710-30	135.19			3.11	6



FLOMATIC® VALVES MODEL 70 - AUTO-DRAIN VALVE™

- Designed for use in domestic well water systems, irrigation and sprinkler systems, agricultural watering
- Provides automatic drainage of water lines when line pressure drops below 10 PSI approx. 5 gpm in a closed water system
- PVC body with stainless steel spring, fasteners and valve disc.
- 1" MPT Connection
- Max Pressure: 400 PSI (27bar)
- Max Temperature: 180°F (80°C)

PART NO.	CTN	CASE	LIST PRICE-A
17-4501P	1	12	90.65

Also available in stainless steel



BOSHART INDUSTRIES

10-6
December 4/15

Telephone: 1-519-595-4444 - Toll Free: 1-800-561-3164
Fax: 1-519-595-4380 - www.boshart.com

FLOMATIC® VALVES MODEL 80 DI - DUCTILE IRON CHECK

- Designed for vertical applications
- High strength epoxy coated ductile iron body, disc and follower
- Threaded female x female connection
- Features a NITRILE (Buna-N) seal, Stainless Steel spring fasteners
- Ductile iron poppet

Note: 1" through 1 1/2" features acetal poppet. 1" - 2" cast steel body

SIZE	PART NO.	WGT lbs	CASE QTY	LIST PRICE-A
1"	174031DI	0.2	49	48.39
1-1/4"	174032DI	0.7	36	67.38
1-1/2"	174033DI †	1.3	25	92.15
2"	177937	5.0	16	179.07
2-1/2"	177936 †	7.0	1	412.63
3"	177938	10.0	5	602.60
4"	177939	19.0	4	928.04
5"	174088 †	48.0	1	1723.72
6"	174089 †	63.0	1	2141.02
8"	174090 †	92.0	1	3618.72

† NON STOCK ITEM PLEASE CALL FOR DELIVERY

To order model 80DI with break off plug add "PLG" to part number

Contact Sales Rep for pricing and delivery.

List price above does not include break off plug.



Temp Max 180°F (80°C)
Pressure Max 400 PSI

FLOMATIC® VALVES MODEL 80DI-VFD CHECK VALVE FOR USE WITH VFD CONTROL PUMPS

New special patent-pending submersible pump check valve for use with variable-frequency drive (VFD) control pumps. Standard check valves will chatter and be noisy when a VFD switches to low flow causing eventual failure. The unique Model 80DI-VFD unit is designed to minimize flow losses and hydraulic shocks in the pumping system. This new, exclusive poppet system insures that the valve smoothly and automatically adjusts to flow and is noiseless at even very low flows.

FEATURES:

- Designed for vertical or horizontal applications
- High strength epoxy coated ductile iron body and poppet.
- Stainless steel guide with threaded female x female 8 round connection.
- Nitrile (Buna-N) seal, stainless steel spring fasteners.



SIZE	PART NO.	WEIGHT lbs	LIST PRICE-A
2"	177937VFD	3	221.11
2-1/2"	177936VFD	9	507.62
3"	177938VFD	15	741.18
4"	177939VFD	25	1139.80
5"	174088VFD	46	2120.78
6"	174089VFD	66	2634.62
8"	174090VFD	93	4453.32

To order model 80DI-VFD with break off plug, add -PLG to part number.
Contact sales rep for pricing and delivery.



Temp Max 180°F (80°C)
Pressure Max
2" - 3" 400PSI
4" - 8" 600PSI

FLOMATIC® VALVES MODEL 80DIX - DUCTILE IRON CHECK

- Similar to model 80DI but features a double-guided ductile iron poppet
- Designed for vertical and horizontal applications


SIZE	PART NO.	WGT lbs	LIST PRICE-A
3"	177938DIX	10.0	512.29
6"	174089DIX	48.0	1736.17
10"	174091DIX	148.0	5551.08

To order Model 80DIX with break off plug, add PLG to part number.
Contact sales rep for pricing and delivery.

List price above does not include break off plug.



Temp Max 180°F (80°C)
Pressure Max 400 PSI



BOSHART INDUSTRIES

Telephone: 1-519-595-4444 - Toll Free: 1-800-561-3164

Fax: 1-519-595-4380 - www.boshart.com

10-7

December 4/15

FLOMATIC® VALVES MODEL 80MDI - DUCTILE IRON CHECK

Similar to model 80DI but features

- Male threaded inlet and female threaded outlet
- 80MDIX Doubled Guided poppet
- Ideal for submersible pumps

NOTE: Port hole one size smaller

SIZE	PART NO.	WGT lbs	CASE QTY	LIST PRICE-A
2" MPT x 2" FPT	174084 †	4.0	16	344.12
3" MPT x 3" FPT	174083 †	8.0	5	540.32
4" MPT x 4" FPT	174077 †	14.0	1	728.73
5" MPT x 5" FPT	174075 †	48.0	1	1270.57
6" MPT x 5" FPT	174087 †	48.0	1	1451.22
6" MPT x 6" FPT	174081 †	40.0	1	1848.29

† NON STOCK ITEM PLEASE CALL FOR DELIVERY

To order Model 80MDI with break off plug add PLG to part number.

Contact sales rep for pricing and delivery.

List price above does not include break off plug.



Temp Max 180°F (80°C)
Pressure Max 400 PSI



FLOMATIC® VALVES BREAK OFF PLUG

- Replacement break-off plug
- Stainless steel construction
- Threaded 3/8" to install into valve
- When broken off, riser pipe drains

SIZE	PART NO.	WGT lbs	LIST PRICE-A
3"	1776098-6	0.20	103.22
4"	1776098-7	0.25	103.58
5" , 6" , 8"	1776098 †	0.30	103.58
10"	1776098-11 †	0.45	124.51

† NON STOCK ITEM PLEASE CALL FOR DELIVERY



FLOMATIC® VALVES MODEL 508 - BALL CHECK

- Cast iron body with epoxy coating
- Threaded female x female connection
- Corrosion resistant phenolic "Sinking" ball
- 2 bolt access cover

SIZE	PART NO.	WGT lbs	LIST PRICE-A
1"	173232 †	3.0	485.81
1-1/4"	173233	4.2	493.91
1-1/2"	173234	5.4	499.31
2"	173235	8.0	607.26
2-1/2"	173236 †	13.8	1454.74
3"	172044 †	30.0	1416.95
4" *	172045 *	45.0	2593.69

† NON STOCK ITEM PLEASE CALL FOR DELIVERY

* CONNECTION IS FLANGED ANSI 125

NOTE: 3" and 4" have no access cover



Temp. Max 180°F (80°C)
Pressure Max 150 PSI



FLOMATIC® VALVES MODELS 208T/208S - PVC BALL CHECK

- Corrosion resistant PVC body
- Threaded female x female connection
- NITRILE (Buna-N) self-cleaning ball
- E-Z access port with nitrile (Buna-N) seal

SIZE	PART NO.	WGT lbs	LIST PRICE-A
1"	172131T	1.0	124.15
1-1/4"	172132T	1.0	107.87
1-1/2"	172133T	2.0	169.36
2"	172134T	2.0	169.36

Also available with socket weld (slip) (Model 208S)

Contact your Sales Rep for information



Temp. Max 150°F (65°C)
Pressure Max 100 PSI



FLOMATIC® VALVES MODEL 208 - BALL CHECK

- Cast iron body with epoxy coating and clean-out port
- Threaded female x female connection
- Features NITRILE (Buna-N) "Sinking" ball

SIZE	PART NO.	WGT lbs	LIST PRICE-A
1-1/4"	172141	4.5	245.60
2"	172142	9.0	315.78



Temp. Max 180°F (80°C)
Pressure Max 150 PSI



BOSHART INDUSTRIES

10-8
August 1/18


Telephone: 1-519-595-4444 - Toll Free: 1-800-561-3164
Fax: 1-519-595-4380 - www.boshart.com

FLOMATIC® VALVES CAST IRON WAFER SPLIT DISC STYLE CHECK VALVE - MODEL 895

- Cast iron body with epoxy coating and split disc design
- Nitrile (Buna-N) seal, PTFE bearing
- Stainless steel spring hinge pin
- Lifting ring standard above 4"
- Sizes 2" to 12" stainless steel disc
- Sizes 14" to 18" bronze disc



Wafer connection ANSI 125
Temp Max 180°F (80°C)
Pressure Max: 200 PSI




SIZE	PART NO.	WGT lbs	LIST PRICE-A	SIZE	PART NO.	WGT lbs	LIST PRICE-A
2"	18SDCVCI-2 †	5	410.24	6"	18SDCVCI-6	21	1068.79
2-1/2"	18SDCVCI-2.5 †	7	480.41	8"	18SDCVCI-8 †	40	1605.88
3"	18SDCVCI-3 †	9	515.50	10"	18SDCVCI-10 †	65	2426.36
4"	18SDCVCI-4	12	663.94	12"	18SDCVCI-12 †	105	3273.83
5"	18SDCVCI-5 †	17	1079.58				


† NON STOCK ITEM PLEASE CALL FOR DELIVERY

FLOMATIC® VALVES CAST IRON GLOBE STYLE SILENT CHECK VALVE - MODEL 402

- Cast iron body with epoxy coating, unleaded bronze disc (up to and including 12") and seat
- Metal to metal seating with stainless steel spring and fasteners



Flanged connection ANSI 125
Temp Max 180°F (80°C)
2" - 12" 200 PSI, 14" - 16" 150 PSI



SIZE	PART NO.	WGT lbs	LIST PRICE-A	SIZE	PART NO.	WGT lbs	LIST PRICE-A
2"	18GSCVCI-2 †	13	938.82	6"	18GSCVCI-6 †	75	2871.69
2-1/2"	18GSCVCI-2.5 †	18	1187.33	8"	18GSCVCI-8 †	116	4694.11
3"	18GSCVCI-3 †	23	1325.40	10"	18GSCVCI-10 †	194	6903.10
4"	18GSCVCI-4	40	1725.78	12"	18GSCVCI-12 †	306	11873.34
5"	18GSCVCI-5 †	51	2747.43				


† NON STOCK ITEM PLEASE CALL FOR DELIVERY

FLOMATIC® VALVES CAST IRON WAFER STYLE SILENT CHECK VALVE

- Cast iron body with epoxy coating, unleaded bronze disc and seat
- Metal to metal seating with stainless steel spring and fasteners



Wafer connection ANSI 125/250
Temp Max 180°F (80°C)
Pressure Max 200 PSI ANSI 125
400 PSI ANSI 250



SIZE	PART NO.	WGT lbs	LIST PRICE-A	SIZE	PART NO.	WGT lbs	LIST PRICE-A
2"	18WSCVCI-2	5	599.19	5"	18WSCVCI-5 †	25	1582.19
2-1/2"	18WSCVCI-2.5 †	7	670.98	6"	18WSCVCI-6 †	36	1656.74
3"	18WSCVCI-3	11	693.07	8"	18WSCVCI-8 †	80	2971.10
4"	18WSCVCI-4	18	902.93	10"	18WSCVCI-10 †	129	4859.78

† NON STOCK ITEM PLEASE CALL FOR DELIVERY

NOTE: 2" - 6" are both ANSI 125/250
8" 250# Flanged
10" ANSI 125 only

BOSHART INDUSTRIES

Telephone: 1-519-595-4444 - Toll Free: 1-800-561-3164

Fax: 1-519-595-4380 - www.boshart.com


10-9

August 1/18

NO LEAD FOOT VALVES

- Available in cast bronze or cast brass body and poppet
- NBR "O" Ring seal (Nitrile Buna-N)

- Stainless steel screen



SIZE	NO LEAD BRONZE		NO LEAD BRASS		QUANTITY		WGT lbs
	PART NO.	LIST PRICE-A	PART NO.	LIST PRICE-A	CTN	CASE	
1/2"	17FV050NL	16.29	17YBFV050NL	11.97	10	100	0.25
3/4"	17FV075NL	19.02	17YBFV075NL	14.75	10	80	0.50
1"	17FV100NL	25.96	17YBFV100NL	20.35	10	60	0.50
1-1/4"	17FV125NL	34.05	17YBFV125NL	28.60	5	40	1.00
1-1/2"	17FV150NL	47.29	17YBFV150NL	40.94	5	30	1.50
2"	17FV200NL	82.28	17YBFV200NL	64.07	5	20	2.25
3"	17FV300NL	367.24	17YBFV300NL	250.13	1	8	6.34
4"			17YBFV400NL	444.06	1	4	12.68



Temp Max 180°F (80°C)
Pressure Max 200 PSI

STAINLESS STEEL FOOT VALVE

Boshart recommends -

Using both Gray Stainless Steel PTFE Tape & Gray Magic Pipe Thread Compound together for joining stainless steel threaded connections.

- #304 Stainless steel body and poppet
- #304 Stainless steel screen
- Viton "O" Ring seal



SIZE	PART NO.	QUANTITY		LIST PRICE-A
		CTN	CASE	
1/2"	17FVSS-050	10	100	23.52
3/4"	17FVSS-075	10	80	27.37
1"	17FVSS-100	10	60	38.36
1-1/4"	17FVSS-125	5	40	49.92
1-1/2"	17FVSS-150	5	30	66.31
2"	17FVSS-200	5	20	117.96
3"	17FVSS-300	1	8	534.58
4"	17FVSS-400	1	4	874.95




Temp Max 180°F (80°C)
Pressure Max 200 PSI

FLOMATIC VALVES MODEL 60SE - FOOT VALVE

- Threaded female connection
- Acetal poppet, Nitrile (Buna-N) seal

- Stainless steel spring and screen
- 2 1/2" , 3" and 4" have bronze poppets

SIZE	PART NO.	WGT lbs	CASE QTY	LIST PRICE-A
1"	17-4101E	0.8	49	68.14
1-1/4"	17-4102E	0.8	49	79.41
1-1/4"	17-4103E	1.0	36	84.08
1-1/2"	17-4104E	1.6	25	135.47
2"	17-4105E	2.1	16	211.77
2-1/2"	17-4106E	6.0	1	699.14
3"	17-4107E †	10.3	1	962.29
4"	17-4108E †	19.0	1	1602.26



Temp Max 180°F (80°C)
Pressure Max 250 PSI



† NON STOCK ITEM PLEASE CALL FOR DELIVERY
Model 17-4102E will pass through a 2" pipe

FLOMATIC VALVES MODEL 63 - CAST IRON FOOT VALVE

- Threaded female connection
- Stainless steel spring
- Acetal poppet (2") Unleaded bronze poppet (2 1/2") Ductile iron poppet (3" - 6")
- Heavy duty polyethylene screen
- Nitrile (Buna-N) seal
- Cast iron body with epoxy coating

SIZE	PART NO.	WGT lbs	LIST PRICE-A
2"	174764	4.0	222.64
2-1/2"	174765	5.0	383.25
3"	174766	9.0	472.32
4"	174767	17.0	609.96
6"	174789	63.0	2415.56



Temp Max 180°F (80°C)
Pressure Max 250 PSI



BOSHART INDUSTRIES

10-10
September 25/17

Telephone: 1-519-595-4444 - Toll Free: 1-800-561-3164
Fax: 1-519-595-4380 - www.boshart.com



PVC FOOT VALVES

- One piece "Extra Heavy Duty" valve body molded from Rigid PVC, listed under NSF61 & NSF14 (ASTM D-1784) provides superior tensile strength.
- FPT threads to ASME /ANSI B 1.20.1 specifications.
- Robust stainless steel poppet and hardware.
- NBR Sealing Gasket ensures a positive seal.
- Flow diverter minimizes turbulence and friction loss.
- Stainless Steel spring closes valve against pressure, eliminating flow reversal & minimizing hydraulic shock.
- Stemless acetel poppet guide for long-lasting, quiet, trouble free operation in both vertical and horizontal installations.
- Polypropylene screen with high open area ensures flow is not restricted.
- Small holes prevent flat pieces of debris/scale from passing thru and into the pumps impeller, a common problem with slotted type screens.
- Tapered screen with rounded nose cone prevents hang-ups on casing during installation.



PART NO.	SIZE	OUTSIDE DIA.	LENGTH	WEIGHT LBS	CARTON QTY	LIST PRICE-A
17PFV075	3/4"	1.598"	3.748"	0.12	20	8.26
17PFV100	1"	1.875"	4.364"	0.175	20	8.75
17PFV125	1-1/4"	2.224"	4.928"	0.285	20	10.45
17PFV150	1-1/2"	2.510"	5.330"	0.36	20	11.53
17PFV200	2"	3.088"	6.086"	0.575	10	16.65
2 in 1 Insert Barb						
17PFVB100125	1" - 1-1/4"	2.04"	7.00"	0.243	20	12.90
4 in 1 MPT Thread						
17PFVM075150	3/4" - 1-1/2"	2.04"	7.45"	0.307	20	13.40

Ratings: Max. Working Pressure: 150 psi at 73°F (1034 kPa @ 22°C), Designed for cold water applications, for hot water applications, special high temperature valves must be used - Consult Factory.

FLOMATIC® VALVES MODEL 193D - PLASTIC FOOT VALVE

- One piece acetel body and strainer
- Nylon 11 poppet
- Stainless steel spring
- Nitrile Buna-N seal




SIZE	PART NO.	WGT lbs	QUANTITY CTN	CASE	LIST PRICE-A
3/8"	175619	0.03	1	10	27.67
1/2"	175620	0.03	1	10	49.00

Temp Max 140°F (60°C)
Pressure Max 150 PSI


PVC FOOT VALVE

- Injection molded PVC body and poppet with screen
- Durable 304 Stainless Steel spring for long lasting operation
- NBR Buna-N seal
- Alkali and acid resistant
- Every Foot Valve is pressure and leak tested
- Tapered screen for easier installation
- Threading: ANSI B1.20.1

Temp Max 140°F (60°C)
Pressure Max 150 PSI at
73°F (22°C)



3" Poppet Design



* Flapper Design

SIZE	PART NO.	ENTERS STANDARD SCHEDULE 40 PIPE SIZE	QUANTITY CTN	CASE	LIST PRICE-A
2-1/2"	17PFV-250	6"	1	12	74.36
3"	17PFV-300	6"	1	12	105.91
3"	17PFVF-300 *	8"	1	6	105.91
4"	17PFVF-400 *	8"	1	6	187.44
6"	17PFVF-600 *	12"	1	2	774.77

BOSHART INDUSTRIES

Telephone: 1-519-595-4444 - Toll Free: 1-800-561-3164

Fax: 1-519-595-4380 - www.boshart.com

10-11

December 4/15

CAST IRON FLAPPER FOOT VALVE

- Cast iron body and strainer
- Hinged leather seat
- Threaded female connection

Temp Max 180°F (80°C)
Pressure Max 250 PSI

Note: Replacement Valve
Leathers are available.
See section 12 for part
numbers and pricing.



SIZE	PART NO.	WGT lbs	VALVE LEA. O.D.	LIST PRICE-A
2"	174964	6.0	4-1/4"	158.16
3"	174966	13.0	5"	350.90
4"	174967	20.0	7-1/4"	495.25
6"	174969	45.0	9-3/4"	1054.38



FLOMATIC® VALVES CAST IRON FLANGED FOOT VALVE

- Cast iron body with epoxy coating, unleaded bronze disc and seat
- Flanged connection ANSI 125
- Vulcanized Nitrile (Buna-N) seal and stainless steel strainer

Temp Max 180°F (80°C)
Pressure Max 200 PSI



SIZE	PART NO.	WGT lbs	LIST PRICE-A
2"	18FLFVCI-2 †	23	2496.53
2-1/2"	18FLFVCI-2.5 †	30	2523.52
3"	18FLFVCI-3 †	37	2537.01
4"	18FLFVCI-4 †	63	2998.54
5"	18FLFVCI-5 †	80	4072.72
6"	18FLFVCI-6 †	100	4572.02
8"	18FLFVCI-8 †	160	6747.38
10"	18FLFVCI-10 †	260	9262.80
12"	18FLFVCI-12 †	410	12954.97

† NON STOCK ITEM PLEASE CALL FOR DELIVERY




FLOMATIC® VALVES NO LEAD BRONZE Y-STRAINER

- 20 Mesh Stainless Steel strainer
- Cast No Lead Bronze body
- Comes with clean-out plug
- Valves are not rated for steam application

Temp Max 180°F (80°C)
Pressure Max 200 PSI



SIZE	PART NO.	WGT lbs	LIST PRICE-A
1/2"	16YS-S-05	1.0	36.19
3/4"	16YS-S-07	2.0	49.26
1"	16YS-S-10	2.0	74.59
1-1/4"	16YS-S-12	3.0	110.78
1-1/2"	16YS-S-15	4.0	152.47
2"	16YS-S-20	8.0	234.16



BOSHART INDUSTRIES

Telephone: 1-519-595-4444 - Toll Free: 1-800-561-3164

Fax: 1-519-595-4380 - www.boshart.com

10-12

December 4/15